



TECHNICAL INFORMATION

Model Number	Approx. Temp.	Voltage	Wattage	Amps
6.5' x 3'	158°F (70°C)	120 VAC	780 Watts	7 Amps
15' x 3'	136°F (58°C)	120 VAC	1440 Watts	12 Amps
6.5' x 6'	158°F (70°C)	120 VAC	1560 Watts	13 Amps

HEATED CURING BLANKETS

Flexotherm™ manufactures custom designed, high quality, curing blankets to help protect the material from harmful elements and to ensure that it cures completely and evenly.

Flexotherm™ Curing Blankets can be custom made to your specifications to ensure the job is done correctly.

FEATURES

- Outfitted with an adjustable thermostat to allow the user to set the exact temperature needed for the job
- High efficiency carbon heating grid evenly distributes heat over the entire blanket area
- Prevents material from cracking, freezing, or accelerated drying
- Heating element technology decreases current as temperature increases
- Constructed of heavy-duty, 18oz vinyl
- Scuff, Water, and UV resistant

INDUSTRIES

- Transportation Bridges
- Concrete
- Ground Thaw
- Concrete Walls
- Structure Beams
- Concrete Curing
- Transportation Systems
- Public Streets
- Concrete Casting
- Construction Applications