

INDUSTRIAL FLEXIBLE DRUM HEATERS



Flexotherm™ produced drum heaters are thin, flexible electrical resistance heaters that can easily be wrapped and secured around drums, pails, and tanks. Every drum heater is made of silicone rubber-reinforced fiberglass cloth, laminated around a nickel alloy circuit. This construction provides an even heat transfer throughout.



FEATURES

- Fits four standard drum sizes
- Metal or non-metal drum versions
- 115V and 230V standard; high wattage 115V configuration available
- 3-prong plug or pigtail termination
- Electrically grounded insulation screen
- Optional adjustment thermostat
- Heavy hook and spring attachment
- Resistant to many chemical substances
- UL recognized and CSA Certified

TECHNICAL INFORMATION

Model Number	Fits Drum Size (gallon)	Drum Material	Wattage
IB-55	55	Metal	None
BXH-55-115-TS	55	Non-Metal	750
BXH-55-230-TS	55	Non-Metal	750
BH-55-115-TS	55	Metal	1000
BH-55-230-TS	55	Metal	1000
BHW-55-115-TS	55	Metal	1500
BHW-55-230-TS	55	Metal	1500

INDUSTRIES

- Biofuel
- Adhesives
- Mastics
- Paints and varnishes
- Oils, fats, and greases
- Epoxy and Resins
- Food and Beverage
- Tar Dispensing
- Spray Polyurethane Foam

INDUSTRIAL FLEXIBLE DRUM HEATERS

Metal Version Drum Heaters have the following prefixes: DH, DHW, DHH; Non-metal version Drum Heaters have the following prefix: XH,

Model Number	Drum Material	Drum Position	Fits Drum Capacity/ Diameter (gal./in.)	Total Wattage (W)	Voltage (V)	Adjustable Thermostat (°F)	Cord Termination	Length / Width (in.)
DH-5-115-TS	METAL	VERTICAL	5 / 11.25	300	115	50 to 425	3-prong plug	30 / 3
DH-15-115-TS	METAL	VERTICAL	15 / 14.25	500	115	50 to 425	3-prong plug	35.88 / 3
DH-30-115-TS	METAL	VERTICAL	30 / 18.25	750	115	50 to 425	3-prong plug	52.50 / 3
DH-55-115-TS	METAL	VERTICAL	55 / 22.5	1000	115	50 to 425	3-prong plug	64.50 / 3
DHW-5-115-TS	METAL	VERTICAL	5 / 11.25	450	115	50 to 425	3-prong plug	30 / 4
DHW-15-115-TS	METAL	VERTICAL	15 / 14.25	750	115	50 to 425	3-prong plug	35.88 / 4
DHW-30-115-TS	METAL	VERTICAL	30 / 18.25	1100	115	50 to 425	3-prong plug	52.50 / 4
DHW-55-115-TS	METAL	VERTICAL	55 / 22.5	1500	115	50 to 425	3-prong plug	64.50 / 4
DH-55-115	METAL	VERTICAL	55 / 22.5	1000	115	NONE	3-prong plug	64.50 / 8
DHH-55-115-TS	METAL	HORIZONTAL	55 / 22.5	500	115	50 to 425	3-prong plug	65.50 / 8
XH-5-115-Ts	NON-METAL	VERTICAL	5 / 11.25	300	115	50 to 160	3-prong plug	29 / 6
XH-15-115-TS	NON-METAL	VERTICAL	15 / 14.25	370	115	50 to 160	3-prong plug	38.5 / 6
XH-30-115-TS	NON-METAL	VERTICAL	30 / 18.25	590	115	50 to 160	3-prong plug	51 / 6
XH-55-115-TS	NON-METAL	VERTICAL	55 / 22.5	750	115	50 to 160	3-prong plug	64 / 6
DH-5-230-TS	METAL	VERTICAL	5 / 11.25	300	230	50 to 425	NONE	20 / 4
DH-15-230-TS	METAL	VERTICAL	15 / 14.25	500	230	50 to 425	NONE	35.88 / 4
DH-30-230-TS	METAL	VERTICAL	30 / 18.25	750	230	50 to 425	NONE	52.50 / 3
DH-55-230-TS	METAL	VERTICAL	55 / 22.5	1000	230	50 to 425	NONE	64.50 / 3
DHW-5-230-TS	METAL	VERTICAL	5 / 11.25	450	230	50 to 425	NONE	20 / 4
DHW-15-230-TS	METAL	VERTICAL	15 / 14.25	750	230	50 to 425	NONE	35.88 / 4
DHW-30-230-TS	METAL	VERTICAL	30 / 18.25	1100	230	50 to 425	NONE	35.88 / 4
DHW-55-230-TS	METAL	HORIZONTAL	55 / 22.5	1500	230	50 to 425	NONE	64.50 / 4
DHH-5-230-TS	METAL	HORIZONTAL	55 / 22.5	500	230	50 to 425	NONE	65.50 / 8
XH-5-230-TS	NON-METAL	HORIZONTAL	5 / 11.25	300	230	50 to 160	NONE	29 / 6
XH-15-230-TS	NON-METAL	HORIZONTAL	15 / 14.25	370	230	50 to 160	NONE	38.5 / 6
XH-20-230-TS	NON-METAL	HORIZONTAL	30 / 18.25	590	230	50 to 160	NONE	51 / 6
XH-55-230-TS	NON-METAL	HORIZONTAL	55 / 22.5	750	230	50 to 160	NONE	64 / 6