



TECHNICAL INFORMATION

| Model | HVB-A-07-500-078-036-08-3-70 | HVB-A-05-350-078-036-08-3-50 |
|----------------------------|-------------------------------------|-------------------------------------|
| Approximate Temperature | 150°F (70°C) | 122°F (50°C) |
| Blanket Dimensions | 36" x 86" (91.44 cm x 218.44 cm) | 36" x 86" (91.44 cm x 218.44 cm) |
| Element Dimensions | 33" x 74" (83.82 cm x 187.96 cm) | 33" x 74" (83.82 cm x 187.96 cm) |
| Wattage | 800 Watts | 555 Watts |
| Amps | 7 Amps | 5 Amps |
| Power | 120 AC | 120 AC |

55 GALLON HEATED DRUM BLANKET

Flexotherm[™] manufactures a custom-designed, high-quality Heated Drum/Barrel blanket for a multitude of industries and applications.

The Flexotherm[™] Heated Drum/Barrel blanket is suitable for a wide variety of plastic, fiber, and metal containers. The blanket offers an even and continuous heat source throughout.

FEATURES

- Outfitted with a GFCI for extra security for both the product and user
- High Efficiency Carbon Heating Grid evenly distributes heat over the entire blanket area
- Heating element, unlike others, decrease current as temperature increases
- Constructed of Heavy Duty Vinyl that is NFPA
 Certified Flame Retardant
- Blankets are outfitted with adjustable retaining straps and quick release plated buckles
- Vinyl Panel Perimeters are sealed with a fully welded seam

INDUSTRIES

- Biofuel
- Petrochemical
- Diesel Exhaust Fluids (DEF) in drums/tanks/ transportation vehicles
- Chemical
- Pharmaceutical

- Military
- Epoxy and Resins
- Food and Beverage
- Tar Dispensing
- Spray Polyurethane Foam

Copyright © 2014 Flexotherm[™], A Neptech Inc. Company 2000 East Highland Road, Highland, MI 48357 810.225.2222 | www.neptechinc.com | www.flexotherm.net