



FILTER HOUSINGS

Flexotherm™ manufactures Electro-polished 316 Stainless Steel Filter Housings for the use of chemical analysis and emissions testing. Our Filter Housings are for use in a heated filter set-up or as a stand-alone filter.

FEATURES

- Available in 1" x 2.5" and 1" x 7" models
- All models made of 316 Stainless Steel
- Electro-polished to reduce hang-up from Ammonia contaminants
- Low internal volume to improve sample response time
- Spring loaded element for easy element exchange
- Positive handle STOP/DETENT to assure proper assembly position
- DuPont Krytox® Performance Lubricant
- Heavy duty Duroplast® Tee Handle with steel shaft insert
- Handle shaft insulated with Teflon®
- High temperature silicone O-Rings located on the removable handle assembly; none required in the base
- 1/4" (0.635 cm) female NPT inlet and outlet ports in the base

OPTIONS


Available Options

Extended Handle Shaft


Dursan SilcoNert® Coating for improved resistance from Ammonia contaminants

Panel Mounting Collar

FILTER HOUSING



Series



Size



Material



Handle Length



Options

Series	F - Filter Housing
Size	2.5 - Element Size 1" x 2.5" (2.54cm x 6.35cm) 7.0 - Element Size 1" x 7.0" (2.54cm x 17.78cm)
Material	EPSS - 316 Stainless Steel
Handle Length	STD - Standard EXT - Extended
Options	DSC - Dursan SilcoNert® Coating Panel Mount PMC - Panel Mount Collar