





TECHNICAL INFORMATION

Model	100°F (38°C) Temperature Model
Approximate Temperature	113°F - 131°F (45°C - 55°C)
Blanket Dimensions	36" x 76" (91.44 cm x 193.04 cm)
Element Dimensions	33" x 74" (83.82 cm x 187.96 cm)
Wattage	632 Watts
Amps	TBD

FLEXIBLE OUTDOOR WORK MAT

Flexotherm[™] manufactures a flexible work mat for a multitude of applications and jobs. The Flexotherm[™] Outdoor Work Mat provides a complete and even heating throughout.

Our blankets are UV, water, and scuff resistant. This allows for our blankets to be perfectly integrated into any type of environment

FEATURES

- Outfitted with a GFCI for extra security for both the product and user
- High Efficiency Carbon Heating Grid evenly distributes heat over the entire blanket area
- Heating element, unlike others, decrease current as temperature increases
- Constructed of Heavy Duty Vinyl that is NFPA Certified Flame Retardant
- Blankets are outfitted with adjustable retaining straps and quick release plated buckles
- Vinyl Panel Perimeters are sealed with a fully welded seam

INDUSTRIES

- Biofuel
- Petrochemical
- Diesel Exhaust Fluids (DEF) in drums/tanks/ transportation vehicles
- Chemical
- Pharmaceutical

- Military
- Epoxy and Resins
- Food and Beverage
- Tar Dispensing
- Spray Polyurethane Foam